

# C DIAMOND TYPE


## INSERTS FOR TURNING

CC-- 7° pos. Inserts for Finishing

80° Diamond Type

7° Relief

With Insert Hole



Dimensions (mm)				
CC--	ℓ	ød (IC)	s	d1
0602--	6,45	6,35	2,38	2,8
09T3--	9,7	9,525	3,97	4,4






⇒ D31

⇒ E14

- P** Steel
- M** Stainless Steel
- K** Cast Iron
- N** Non-Ferrous Metals
- S** Super Alloy
- H** Hardened Steel

### CCGT

#### ● G-Class Handed and Bumpy Chipbreaker

Application	Shape	ISO Cat. No.	r	AC	AC	AC	AC	AC	AC	AC	AC	AC	AC	AC	AC	AC	AC	AC	T15	T20	T30	T10	T15	G1	EH	EH	H
Finishing	 NFC	CCGT 060201M NFC CCGT 060202M NFC CCGT 060204M NFC	<0,1 <0,2 <0,4																●			○	○				
		CCGT 09T301M NFC CCGT 09T302M NFC CCGT 09T304M NFC	<0,1 <0,2 <0,4																●			○	○				
Finishing	 L/RFX	CCGT 0602003 LFX CCGT 060201 LFX CCGT 060202 LFX CCGT 060204 LFX	0,03 0,1 0,2 0,4																○	●	▲	●	●				
		CCGT 09T301 LFX CCGT 09T302 LFX CCGT 09T304 LFX CCGT 09T308 LFX	0,1 0,2 0,4 0,8																○	●	▲	●	●				
Finishing	 RFX	CCGT 0602003 RFX CCGT 060201 RFX CCGT 060202 RFX CCGT 060204 RFX	0,03 0,1 0,2 0,4																○	●	▲	●	●				
		CCGT 09T301 RFX CCGT 09T302 RFX CCGT 09T304 RFX CCGT 09T308 RFX	0,1 0,2 0,4 0,8																○	●	▲	●	●				

- = Euro stock
- = Japan stock
- ▲ = To be replaced by new item